

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
20 January 2005 (20.01.2005)

PCT

(10) International Publication Number
WO 2005/004657 A1

(51) International Patent Classification⁷: A43B 13/20, 7/06

[KR/KR]; 29-245, Gamman-dong, Nam-gu, Busan City 608-070 (KR).

(21) International Application Number:

PCT/KR2004/001198

(74) Agents: PARK, Wonyong et al.; 5 Floor, Shinwon Bldg., 823-14, Yeoksam 1-dong, Gangnam-gu, Seoul 135-933 (KR).

(22) International Filing Date: 21 May 2004 (21.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

10-2003-0047493 12 July 2003 (12.07.2003) KR

(71) Applicant (for all designated States except US): E & O KOREA CO., LTD. [KR/KR]; 5 Floor, 204-6, Nonhyeon 1-dong, Gangnam-gu, Seoul Metropolitan City 135-826 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AI, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (for US only): LEE, Kwangsoo

[Continued on next page]

(54) Title: PUMPING DEVICE OF SHOES



(57) Abstract: The present invention discloses a pumping device of a shoe 100 includes a cushion body (110) formed inside a sole of the shoe (110) and having front and back air chambers (120 and 130) formed therein in such a manner as to be disposed at the front and back portions thereof; an automatic pump (140) mounted adjacent to the back air chamber (130) in such a manner as to communicate with the back air chamber (130) and having a height (H2) higher than a height (H1) of the back air chamber (130); a suction valve (150) and a check valve (160) mounted at the front and back sides of the automatic pump (140); and a pressure adjusting valve (170) formed at a connecting valve (125) for connecting the back air chamber (130) with the front air chamber (120).

WO 2005/004657 A1

European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*